

型号	额定容量(KVA)	损耗		阻抗电压(%)	空载电流(%)	重量(kg)			尺寸(mm)			轨距(mm)	
		空载(W)	负载(W)			器身	油重	总重	L	W	H	D	E
S9-M-30/10	30	130	600		2.1	175	100	360	1065	665	1000	400	550
S9-M-50/10	50	170	870		2.0	235	110	430	1095	675	1060	400	550
S9-M-63/10	63	200	1040		1.9	270	130	520	1125	685	1100	400	550
S9-M-80/10	80	250	1250		1.8	310	150	590	1155	695	1130	400	550
S9-M-100/10	100	290	1600		1.6	350	155	640	1155	705	1170	400	550
S9-M-125/10	125	340	1800		1.5	400	185	750	1225	735	1180	400	550
S9-M-160/10	160	400	220		1.4	480	195	840	1235	745	1230	550	550
S9-M-200/10	200	480	2600		1.3	550	230	980	1365	825	1260	550	550
S9-M-250/10	250	560	3050		1.2	680	265	1160	1405	845	1330	550	650
S9-M-315/10	315	670	3650		1.1	815	295	1370	1445	850	1370	550	650
S9-M-400/10	400	800	4300		1.0	960	360	1620	1515	905	1450	550	750
S9-M-500/10	500	960	5100		1.0	1140	405	1880	1585	935	1480	600	750
S9-M-630/10	630	1200	6200		0.9	1275	470	2110	1700	970	1540	660	850
S9-M-800/10	800	1400	7500		0.8	1650	520	2590	1720	985	1640	660	850
S9-M-1000/10	1000	1700	10300		0.7	1800	625	2940	1890	1130	1690	820	850
S9-M-1250/10	1250	1950	12000		0.6	2180	685	3420	1870	1070	1750	820	850
S9-M-1600/10	1600	2400	14500		0.6	2595	790	4010	1925	1105	1810	820	900
S9-M-2000/10	2000	2800	17800		0.6	3170	860	4930	2080	1220	2070	820	820