

技术参数和外形尺寸

高压额定电压	(10,10,5)10(6,6,3,6)KV	低压额定电压	0.4KV
绝缘水平	LI75AC35/LI0AC3	联结组别	DYn11,Yyn0

型号	损耗		空载 电流	噪音	重量	尺寸(mm)												
	空载 (W)	负载 (120%)				10 %	LP Db	GT Kg	a	b	c	d	e	f	g	gl	h	i
SC9-50/10	260	820	4	1.42	46	400	1100	1000	1100	550	960	840	230		300		300	150
SC9-80/10	290	913		1.39	46	450	1200	1000	1200	550	970	850	215.5		290	250	320	160
SC9-100/10	387	1264		1.14	48	600	1200	1000	1300	550	1040	875	226.5		301	250	340	170
SC9-125/10	420	1450		1.1	48	700	1200	1000	1300	550	1080	895	227.5		303	250	350	180
SC9-160/10	480	1670		0.97	48	820	1300	1000	1300	550	1100	955	232.5		310	250	360	180
SC9-200/10	579	1891		0.78	50	960	1400	1100	1400	660	1155	1017	239.5		354.5	250	380	190
SC9-250/10	613	2228		0.62	50	1170	1400	1100	1500	660	1230	1090	250.5		365.5	250	395	210
SC9-315/10	751	2269		0.63	50	1770	1500	1100	1500	660	1265	1116	257		372	250	410	210
SC9-400/10	892	3196		0.61	51	1490	1600	1100	1600	660	1415	1175	262		377	250	410	210
SC9-500/10	1038	3565		0.52	51	1860	1600	1100	1650	660	1415	1260	276.5		395	280	440	200
SC9-630/10	1176	4465		0.47	51	2050	1600	1100	1650	660	1450	1290	280.5		400	280	450	220
SC9-800/10	1529	5371		0.54	51	2285	1700	1200	1800	820	1547	1390	270.5		395	280	460	230
SC9-1000/10	1545	6603		6	0.31	51	2720	1700	1200	1900	820	1652	1435	266.5		391	350	495
SC9-1250/10	1825	7516	0.39		52	3230	1900	1300	1900	820	1637	1430	270.5		395	350	535	270
SC9-1600/10	2175	9046	0.36		52	3940	2000	1300	2000	820	1747	1532	291		415	350	575	290
SC9-2000/10	2448	10682	0.31		53	4900	2100	1300	2200	820	1967	1730	296		421	350	600	300
SC9-2500/10	3033	13754	0.42		53	5600	2100	1300	2300	820	2047	1740	266		444	350	630	320