



SC Cable Lug

Application

SC cable lugs are suitable for the connection of copper conductors (section 1.5–1000mm²) in power cable with electronic equipment. They are made of higher 99.9 percent pure copper tube T2 and coated with tin. Working temperature is from -55°C to +150°C.

Technical specification

Model	φ	D	d	L
SC-1.5	φ4, φ5	3.5	1.8	1.8
SC-2.5	φ4, φ5, φ6	4	2.5	19
SC-4	φ5, φ6	4.8	3.1	21
SC-6	φ5, φ6, φ8	5.5	3.8	24
SC-10	φ6, φ8	6.8	4.8	25.5
SC-16	φ6, φ8, φ10	7.5	5.5	30.5
SC-25	φ6, φ8, φ10, φ12	9	7	34
SC-35	φ8, φ10, φ12	10.5	8.2	38
SC-50	φ8, φ10, φ12	12.5	9.8	45
SC-70	φ8, φ10, φ12	14.5	11.5	50
SC-95	φ10, φ12	17.5	13.8	55.5
SC-120	φ12, φ16	19.5	15.5	63
SC-150	φ12, φ16	20.5	16.5	71
SC-185	φ16	23.5	18.8	78
SC-240	φ16	26	21	92
SC-300	φ12, φ20	30	24	102
SC-400	φ16, φ20	34	27	113
SC-500	φ16, φ20	38	30	123
SC-630	φ20	45	35	135
SC-800	φ22	50	40	170
SC-1000	φ22	56	44	200



A Wintersweet Type Red Copper Jointing Clamp

Application

It is suitable for transition connection of the electric appliances of indoors distributing device and kinds of wire cables. It adopts T2 red copper, the surface nickel plating.

Technical specification

Type	L	L1	B	B1	H	H1	D	M
A16-25	39.5	15	25	16.5	13	13	8.5	5
A16-25	45	15	22	18	13	13	8.5	5
A25-35	52.5	15	24.5	21.2	13.5	13.5	10.5	5
A50-70	61	21	31	23	18.5	18.5	10.5	6
A70-95	69	24	35	23.5	20	20	10.5	6
A95-120	74	20.5	42	28.5	22.5	22.5	13.5	7
A120-150	73.5	30	41	27	24	24	13.5	8
A150-185	76	30	42	28	24.5	24.5	13.5	8
A185-240	80	32	44	30	25	25	13.5	8

