

型号	额定容量 (KW)	负载损耗 (KW)	空载电流 (%)	阻抗电压 (%)	总重 (t)	运输总重 (t)	总油重 (t)	上节吊重 (t)	外形尺寸(mm)						
									A	B	L	W	H	M	L1
SFZ9-6300/110	11.5	41	0.95	10.5	20.84	18.37	6.6	1.9	1475	1475	4695	3190	4200	1100	1630
SFZ9-8000/110	13.2	50	0.90		22.82	20.00	7.2	2.15	1475	1475	4765	3280	4350	1165	1650
SFZ9-10000/110	15.2	59	0.85		24.08	21.23	8.0	2.32	2040	1475	4650	3615	4580	1150	1660
SFZ9-12500/110	17.5	70	0.80		27.84	24.4	8.1	2.71	2040	1475	4870	4100	4490	1205	1660
SFZ9-16000/110	20.5	86	0.75		32.52	28.72	8.9	3.04	2040	1475	5100	4400	4550	1250	1710
SFZ9-20000/110	23.5	104	0.75		37.55	32.89	11.04	3.12	2040	1475	5150	4900	4450	1440	1750
SFZ9-25000/110	27.0	123	0.65		41.05	37.47	10.84	4.43	20.40	1475	5300	4680	4780	1245	1760
SFZ9-31500/110	31.0	148	0.60		54.6	47.18	13.8	4.73	20.40	1475	5590	4830	5200	1290	1960
SFZ9-40000/110	37.0	174	0.55		59.1	52	14.5	5.02	20.40	1475	6100	5400	5500	1255	1998
SFZ9-50000/110	44.0	216	0.50		68	59.3	16.5	5.32	20.40	1475	6300	4970	5600	1295	1990
SFZ9-63000/110	56.0	260	0.45		73.79	63.99	18.1	6.2	2040	1475	6390	5260	5710	1350	2010