









## XCK-P型系列

XCK-P/XCK-T	XCK-P model double insulation, according to CENELEC EN50047 on-line incoming mouth.					
	Metal head direct-acting type	Steel-head with rubber cover direct-acting type	Thermoplastic roller direct-acting type	Thermoplastic roller tumbler direct-acting type. Single direction with horizontal movement	Thermoplastic roller tumbler direct-acting type. Single direction with vertical movement	Thermoplastic roller tumbler direct-acting type. Single horizontal and vertical movement
 2-pole contact terminal Quick  2-pole contact terminal Slow						
Machine life (million times)	15	15	10	15	15	15
(m/s) Motion speed (m/s)	0.5	0.5	0.3	1	1	1
Protection degree	IP653					
Rated work characters	ALTIPAK AC 15; A 300 (Ue=240V Ie=3A) / ALTIWAR DC 13; Q 300 (Ue=250V Ie=0.27A)					
Boundary dimensions: width × depth × height	30 × 30 × 7					
Complete switch (2 poles 1-close+1-open, quick)	XCK-P110	—	XCK-P102	XCK-P121	XCK-P127	XCK-P128
Complete switch (2 poles 1-close+1-open, Cut off at first then connect, cut off slowly)	XCK-P510	XCK-P511	XCK-P502	XCK-P521	XCK-P527	XCK-P528